

Driver guide

Driver set for		1-10V (pot)	DALI	ZigBee
Libra Pyxis Corvus	350mA	+11480031 Driver set 1	+11480034 Driver set 4	+11480037 Driver set 7
Ara 2 Ara 3	500mA	+11480032 Driver set 2	+11480035 Driver set 5	+11480038 Driver set 8
Ara 1	700mA	+11480033 Driver set 3	+11480036 Driver set 6	+11480039 Driver set 9

Can power up to 8 LEDs.. Plug-and-play LED driver set with plugs for simple mounting. Tested and selected for optimum results with these luminaires. Supplied assembled: LED driver with power supply cord (2m) and JST RCY connector. Connector cable length: 60 cm.

*for less than 4 LEDs, X number of jumpers must be purchased (+11080010)
Other driver solutions are available on request.



+11480031



+11080010

NB.

Risk with higher currents: LED damage; drastically reduced lifetime; luminaire failure

Driver power rating can vary +/- 10% from nominal value

Risk with drivers not compliant with ratings: LED damage; flickering; permanently reduced light output

For consistently well-defined light output, always connect the fixtures in series

For non-standard wires or >8 splits per driver, calculate for electronic loss in the wires

Full driver product range and selection data available at www.rob-light.com

Driver guide

Driver wiring guide

