


The Wheel Kit can produce various spectacular scenarios. It has a sparkling and twinkling effect which generates a dynamic result. The Kit can create a starry sky. It has a standard speed of 1 rpm. Other speeds are available on request. If specified it is possible to fully or partly combine the Twinkle Wheel Kit with colours to creat spectacular effects in ceilings and floors or to include water feature lighting into side light fibres for optimum effect.

Roblight A/S, Gl. Skagensvej 105 H, DK-9900 Frederikshavn, T: +45 9244 4888, E: info@rob-light.com, www.rob-light.com

- For indoor use / dry locations
- External electronic driver
- Black painted finish
- Standard speed of 1 rpm
- Light port: Ø9/Ø28 mm



Wheel kit

▼CERoHS

IP 20

Connector size	Ø9/Ø28
Wheel type	Twinkle wheel / Colour Wheel
Colours and colour order	White (clear)-purple-yellow-green-orange-blue-red-dark blue
Divisions	8
Size	127 x 110 x 86 mm
Colour	Black
Supply voltage	230 V / 50 Hz Volt
Total power	4 W
Power cord	Supply cord w/ 2 conductors
Driver type	Magnetic
Max. ambient temperature	40 °C
Min. ambient temperature	-20 °C
Protection rating	IP 20
Material	Aluminium
Surface treatment	Anodised

	Item no.
Colour Wheel kit - 8 colours	0126 6106
Twinkle Wheel kit	0126 6206

RobLight A/S, Gl. Skagensvej 105 H, DK-9900 Frederikshavn, T: +45 9244 4888, E: info@rob-light.com, www.rob-light.com