

## XPO X-LED series

---

### Wall to Wall

---






XPO X-LED Horizontal is the perfect choice for your interior environment if you are aiming for a sublime light in your showcases, niches, exhibition or display areas.

It includes a warm white light solution and it has high colour rendering. Dimmable options are also available. The finish is black or grey.

Other finishes are obtainable on request. XPO X-LED Horizontal stands on 8mm legs and can be mounted on vertical or horizontal surfaces.

Its measurements are customized according to your specific needs.

- For indoor use / dry locations
- White light 3.000K
- External electronic driver
- Dimmable versions available
- Black or aluminium finish
- Surface treatment, Anodised



Mounting bush

- IP 20
- 0,7kg/m
- ±150°
- 360°



|                            |                                 |
|----------------------------|---------------------------------|
| Material                   | Aluminium, plastic and other    |
| Size W                     | Ø26 x min. 180 mm - max 1860 mm |
| Colour                     | Black and grey                  |
| Rotation                   | ±150°                           |
| Total power consumption    | 24V DC                          |
| Driver mode                | Constant voltage                |
| Driver lifetime, expected  | >50.000h                        |
| Supply voltage (mains)     | 100-240V 50-60Hz                |
| LED power consumption      | 7.5W/m                          |
| LED efficacy               | 100 lm/W                        |
| LED lifetime, expected     | >50.000h @Ta=25° C              |
| Fixture luminous flux      | 720 lm/m                        |
| Dimmer systems applicable  | 1-10V, PUSH (mains)             |
| Cooling system             | Natural convection              |
| Ambient temperature        | -20° to 45° C Max               |
| Lumen maintenance          | L70 B0 after 50.000h            |
| Applied LED                | Xicato                          |
| CCT (nominal)              | 3000K, other CCT on request     |
| CRI-8 (Ra) typical value   | Min. 98                         |
| Transmission through cover | 53%, 80%, 93%                   |
| Cleaning                   | Dry cloth or air                |

|                              | Item no.  |
|------------------------------|-----------|
| XPO X-LED Wall to Wall black | 1207 0210 |
| XPO X-LED Wall to Wall grey  | 1207 0220 |